

### DESCRIPTION

Upgrade existing CAMPO luminaires with this LED Upgrade Kit, designed to seamlessly convert legacy fixtures to modern, high-performance LED technology. This all-in-one solution simplifies retrofits while delivering improved efficiency, reliability, and long-term performance. The kit includes a precision-engineered LED light engine with mounting plate, optimized reflector optics, a tray-mounted LED driver, and all required mounting hardware for quick and secure installation. Suitable for use in all Campo 450 wall or pole-mounted models.



|                     |             |                       |
|---------------------|-------------|-----------------------|
| Date: _____         | Type: _____ | Catalog Number: _____ |
| Project Name: _____ |             |                       |

### ORDERING INFORMATION

| LED UPGRADE KIT                        |                       |              |                         |                 |
|----------------------------------------|-----------------------|--------------|-------------------------|-----------------|
| MODEL                                  | OUTPUT                | CCT          | CONTROL                 | VOLTAGE         |
| CA450-KIT<br>Campo 450 LED Upgrade Kit | SO<br>Standard Output | 30K<br>3000K | DIM<br>0-10v<br>Dimming | UNV<br>120-277V |
|                                        | HO<br>High Output     | 40K<br>4000K | ON-OFF<br>On/Off        |                 |

Custom options are available; consult factory for assistance via phone at (864) 487-3535 ext. 258 or via email at DesignServices@EXP-Brands.com.

### SPECIFICATIONS

#### DESCRIPTION

LED kit consists of LED engine with reflector optics and tray mounted driver.

#### OPTICS

Single COB LED is positioned within specular anodized aluminum reflector, laser cut for precise reproduction.

#### ELECTRICAL

Universal driver accepts input voltage range from 120v to 277v at 50/60Hz. Power consumption is 28 watts for standard output or 42 watts for high output model. Power factor is greater than 0.95.

#### DELIVERED LUMENS / SYSTEM WATTS / BUG RATING

##### Standard Output: 28 Watts

3000K: 1326 lumens / B0-U3-G2                      4000K: 1644 lumens / B0-U3-G2

##### High Output: 42 Watts

3000K: 2040 lumens / B0-U3-G2                      4000K: 2530 lumens / B0-U3-G3

NOTE: Due to rapid and continuous advances in LED technology, LED luminaire data is subject to change without notice and at the discretion of HessAmerica. Consult factory for current technical data.

#### CERTIFICATION

CSA Certified for Wet Locations

#### WARRANTY

Limited product warranty period including the LEDs is five years. LED driver shall carry the respective manufacturer's limited warranty.