

FARINO S

Compact Square Spotlight

.hess

DESCRIPTION

Farino is a highly versatile and compact square spotlight featuring the efficient LEVO-C LED module capable of delivering up to 3200 lumens. Lighting options range from narrow, medium, or wide beam angles, 4 static white CCTs, and standard or high output power levels, and it is powered by a remote mounted dimming driver for flexible installation. Farino is an integral component featured in Hess's Shadow Lights and Mosaic Montage Spot series. Housing is heavy-duty aluminum, IP65 rated, and is finished in a finely textured Primar® coating for demanding exterior conditions. A Round Farino is also available.



Date: _____ Type: _____ Catalog Number: _____

Project Name: _____

ORDERING INFORMATION

LUMINAIRE							
MODEL	OUTPUT	CCT	CONTROL	INPUT VOLTAGE	OPTIC	FINISH	OPTIONS
FARINO-S Square Farino Floodlight	SO Standard Output	27K 2700K	DIM 0-10v Dimming	UNV 120-277v	NB Narrow Beam 30°	BL Black	SNOOT Snoot
	HO High Output	30K 3000K			MB Medium Beam 50°	DB Dark Bronze	VISOR Visor
		35K 3500K			WB Wide Beam 65°	DG Dark Grey	LVR Louver
		40K 4000K				GG Graphite Grey	
						SG Silver Grey	
						CC Custom RAL Color	

Custom options are available; consult factory for assistance via phone at (864) 487-3535 ext. 258 or via email at DesignServices@EXP-Brands.com.

SPECIFICATIONS

HOUSING

Housing and trim plate are cast aluminum. Extruded and machined adjustable mounting bracket provides 60° up/down and 30° left/right adjustability, set in place via set screw. Self contained LED light module is gasketed and sealed for weathertight performance. LED light engine is thermally managed with open air heat sink that is built into the housing for optimal heat dissipation. Heat sink is extruded aluminum. All hardware is stainless steel.

MOUNTING

Custom mounting brackets are ordered separately and are available on request. Consult factory for assistance.

OPTICS

Light engine consists of a field replaceable aluminum core PCB with four high-power LEDs and a single piece lens molded from optical quality acrylic. Fixed beam optics are available in Narrow 30°, Medium 50°, or Wide 65° beams. Lens efficiency is 80%. Color temperature may be 2700K, 3000K, 3500K, or 4000K, with additional options available on request. CRI is 80. A snoot, visor, and honeycomb louver are available for additional optical control.

LED DELIVERED LUMENS / WATTS

Standard Output: 1920 Delivered Lumens / 20 Watts

High Output: 3168 Delivered Lumens / 33 Watts

NOTE: Due to rapid and continuous advances in LED technology, LED luminaire data is subject to change without notice and at the discretion of HessAmerica. Consult factory for more current technical data. Final photometry is pending.

ELECTRICAL

Luminaire features a remote mounted driver offering 0-10v dimming control. Input voltage range is 120v through 277v at 50/60Hz. Two power levels are available: Standard Output, consuming 20 Watts, and High Output, consuming 33 Watts. LED driver shall be UL recognized.

FINISH

Luminaire is finished in finely textured matte silver grey metallic, dark grey, graphite grey, matte black, or dark bronze. Custom RAL colors available on request. Hess standard textured finishes feature proprietary PRIMAR® protective coating for long-term corrosion and UV protection.

CERTIFICATION

NRTL Certification Pending

INGRESS PROTECTION

IP65

WARRANTY

Limited product warranty period including LEDs is five years. Driver shall carry the manufacturer's limited warranty.

CUSTOMIZE YOUR **EX**PERIENCE.

At Experience Brands, we believe every space deserves unique lighting elements. We proudly specialize in crafting solutions that reflect your personal vision. Our expert team is here to collaborate with you to design and implement customized features that elevate your environment.

Ready to Get Started? Email us at: DesignServices@exp-brands.com

FARINO S

Compact Square Spotlight

.hess

DIMENSIONS

All dimensions are shown in inches unless otherwise noted.

