

DESCRIPTION

Simplicity defines the refined detailing of the PARIS barrier bollard. The grooved top cap is precision machined from billet aluminum and press fit into the shaft. Steel shaft with subtle base reveal is hot-dip galvanized for long-term corrosion resistance. Two heights are available with a variety of mounting styles including embedded, removable flange mount, and collapsible models. Bollard is finished in finely textured paint. Standard colors; matte silver grey metallic, dark grey, graphite grey, black, or dark bronze. Special RAL colors available. All hardware is stainless steel.

PROTECTED BY

PRIMAR®



Date: _____ Type: _____ Project: _____

Catalog Number: _____



ORDERING INFORMATION

BOLLARD			
MODEL	MOUNTING	FINISH	OPTIONS
PR1100 3.5' Paris 1100 Barrier Bollard	C Collapsible Bollard	BL Black	CH1 Chain Holder on One Side
PR900 3' Paris 900 Barrier Bollard	R Removable Bollard	DB Dark Bronze	CH2 Chain Holder on Two Sides
	E Embedded Bollard	DG Dark Grey	PK Pentagon Key for Emergency Vehicle Access (for Collapsible or Removable Bollards)
	F Flange-Mounted Bollard	GG Graphite Grey	RCP Removable Cover Plate (for Removable Bollards Only)
		SG Silver Grey	
		CC Custom RAL Finish	

Custom options are available; consult factory for assistance via phone at (864) 487-3535 ext. 255 or via email at DesignServices@EXP-Brands.com.

MOUNTING KITS (Required, Ordered Separately)

PR900-1100-SI-REM
Removable Paris Mounting Kit - Soil Insert (for embedment into concrete)

PR900-1100-SI-COL
Collapsible Paris Mounting Kit - Soil Insert (for embedment into concrete)

SPECIFICATIONS

HOUSING

Straight round bollard shaft is manufactured from cold drawn over mandrel, electric-weld, mechanical round steel tubing with nominal wall thickness of 0.126". Diameter of shaft is 4". Steel shaft is hot-dip galvanized prior to painting. Grooved top cap is machined from 6082 aluminum and press fit securely into the shaft. Bollard is finished in finely textured paint.

MOUNTING

Bollard is available with four mounting types:

COLLAPSIBLE - Collapsible bollard includes hot-dip galvanized steel insert for embedment into concrete to receive bollard. Bollard is installed or removed via key-activated internal steel rod that engages with the insert. Bollard is hinged at the base.

REMOVABLE - Removable bollard includes hot-dip galvanized steel insert for embedment into concrete to receive bollard. Bollard is installed or removed via key-activated internal steel rod that engages with the insert.

EMBEDDED - Bollard includes additional shaft length of 19.7" for embedment into a concrete foundation (by others).

FLANGE MOUNT - Flange model mounts to concrete foundation by others. Mounting hardware by others.

DIMENSIONS

PR1100: 43.3" H x 4"

PR900: 35.4" H x 4"

FINISH

Housing is cleaned ultrasonically prior to painting. Standard finishes are finely textured matte silver grey metallic, dark grey, graphite grey, matte black, or dark bronze. Special RAL colors available on request. Hess standard textured finishes feature proprietary PRIMAR® protective coating for long-term corrosion and UV protection.

WARRANTY

Limited product warranty is 5 years.

DIMENSIONS

Note: Bollard design may differ slightly from dimensional drawing below.

