

RIVA 650

Wall Mounted Luminaire

.hess

DESCRIPTION

Wall mounted luminaire is precision-machined from billet aluminum, then satin anodized. The translucent matte acrylic lens provides diffused illumination. Inverted tapered cast aluminum housing is finished in finely textured paint. All hardware is stainless steel.

PROTECTED BY
 **PRIMAR**®



Date: _____	Type: _____	Catalog Number: _____
Project Name: _____		

ORDERING INFORMATION

LUMINAIRE					
MODEL	CCT	CONTROL	VOLTAGE	FINISH	OPTION
RV650W RIVA 650	30K 3000K	ON-OFF On-Off	UNV 120-277V	DG Dark Grey	AP Adapter Plate for Mounting Over 4" Octagonal Box
RV650WG RIVA 650 With 12° Tilt	40K 4000K	DIM 0-10v Dimming		GG Graphite Grey	
	A Amber			SG Silver Grey	
	B Blue			BL Black	
	G Green			DB Dark Bronze	
	R Red			CC Custom RAL Color	

SPECIFICATIONS

HOUSING

One-piece luminaire base is precision-machined from 6060 billet aluminum, then satin anodized. Cylindrical matte acrylic lens with two guide pins twists and locks onto luminaire base and is secured with three button head cap screws. One-piece closed cell silicone gasketing provides a weather-tight seal. Luminaire base fastens to the one-piece cast aluminum tapered housing with three recessed setscrews and is sealed with one-piece closed cell silicone gasket. LED driver mounts to plate on the underside of the housing and housed in the top of the bracket. All hardware is stainless steel.

RV650WG wall bracket has 12° tilt away from wall surface.

OPTICS

Single CoB LED is positioned within the cylindrical matte acrylic lens producing symmetrical distribution.

ELECTRICAL

LED driver consumes 12.5 watts and is integral to the inverted taper wall bracket. Input voltage to driver is 110v through 277v AC with 50-60 Hz. Driver shall be UL recognized.

LED DELIVERED LUMENS / SYSTEM WATTS / BUG RATING

3000K: 1387 LMS / B0-U4-G1

4000K: 1495 LMS / B0-U4-G1

NOTE : Due to rapid and continuous advances in LED technology, LED luminaire data is subject to change without notice and at the discretion of HessAmerica. Consult factory for current technical data.

MOUNTING

Tapered cast aluminum housing with integral arm mounts over single gang switchbox and is secured to surface with four factory supplied socket head lag screws and anchors. Optional adapter plate to mount standard luminaire over 4" octagon box is available upon request.

FINISH

Luminaire base is satin anodized aluminum. Standard finishes for cast aluminum housing are finely textured dark grey, graphite grey, silver grey, black, or dark bronze. Special colors available on request.

WEIGHT: 6 lbs

CERTIFICATION

UL Listed for Wet Locations

WARRANTY

Limited product warranty period including the LEDs is five years. Driver shall carry the manufacturer's limited warranty.



RV650WG

All dimensions are shown in inches unless otherwise noted.



RIVA 650

Wall Mounted Luminaire

.hess

APPLICATION

